

belt foam bar

BFS-BA-48



the good stuff

- **save on cost and labor**
belt foam bars save time, chemical costs, and labor, no more hand-spraying lines.
- **complete belt coverage**
foam offers visual confirmation of up to 4ft of chemical coverage on full belt rotation.
- **flexible mounting**
 - fits existing belt equipment and adjusts cleaning heights to meet your specific needs.

features

- reduced chemical and water consumption because of foam
- contact time contributes to soil breakdown
- consistent coverage
- provides visual cleaning
- belt foam bars make belt cleaning quicker and more affordable
- easy mount bracket to conveyor
- can clean the top surface and inside the belt
- can be used as part of the Clean-in-Place process

industries

- food and beverage
- industrial



how to buy

specifications

- **output volume**..... With 3/4 in. (19 mm) hose:
25-30 gal/min (95-114 l/min)
- **flow rate**..... With 3/4 in. (19 mm) hose:
2-2.25 gal/min (7.6-8.5 l/min)
- **coverage area**..... 4 ft. (1.2 m) width beneath the bar
- **attachment head size and type**..... 4 ft. (1.2 m) long 3.4 in. (19 mm) PVC pipe

requirements

- **liquid temperature range**..... 40-100 ° F (4.4-37 ° C)
- **equipment requirements**.....
requires connection to a FOAMit unit with 3/4 in. (19 mm) discharge hose and a 1/2 in. FPT discharge ball valve
- **chemical compatibility**..... chemical products used with this equipment must be formulated for this type of application and compatible with unit materials and pump seals. For more information on chemical compatibility, consult the manufacturer or SDS for your product or contact our customer service department.