

Drain Foaming Attachment

DFA-D12-48 & DFA-D12-36



The Good Stuff

- **Small size, big foam**
Same high quality foam output FOAMit is known for in a small convenient unit
- **Foam anywhere**
When you need to clean specific surface, our pump up foam unit is there. Apply foam even when the unit is upside down
- **Comfortable & ergonomic**
Thumb trigger built into our handle eliminates carpal tunnel stress common with old fashioned trigger-pull units. Switch and save your wrists

Features

- Provides 360° contact along pipe walls
- Stainless steel foam disc to cover drains up to 12 inches (30.5 cm) in diameter
- Rubber stopper to plug drains 3.5 to 5 inches (8.9-12.7 cm) in diameter
- Stainless steel construction
- Connects to compatible FOAMit units using included quick-connect fittings

Options

- Size options
 - 48 inches
 - 36 inches

Industries

- Institutional
- Food and Beverage
- Manufacturing

Specs

- **Attachment head size and type**.....
STAINLESS STEEL FOAM DISC: covers drains up to 12 in. (30.5 cm) in dia.
RUBBER STOPPER: plugs drains 3.5 to 5 in. (8.9-12.7 cm) in dia.

Requirements

- **Requirements**..... Requires connection to a FOAMit unit with a ½ in. FPT discharge ball valve
- **Chemical compatibility**.....chemical products used with this equipment must be formulated for this type of application and compatible with unit materials and pump seals. For more information on chemical compatibility, consult the manufacturer or SDS for your product or contact our customer service department.



How to Buy



800 567 5420 | sales@foamit.com