
Twin Line Central Doorway Foam Station



DS-WSTN-TL



Features

- One central pump distributes pre-mixed solution through header system
- · Pump and doorway nozzles sold separately
- Up to 100 ft. (30.5 m) total distance between control box and nozzle(s) (Note: distance does not need to be evenly distributed)
- · Powered by air and electricity
- · Repeat cycle timer

Industries

- · Food and Beverage
- Manufacturing



How to Buy

The Good Stuff

• Secure central chemical location

Keep chemistry secure, away from the production floor; no need to refill containers, chemistry given on demand

No refills

One location to titrate consistent chemical

On schedule chemical delivery

Repeat cycle timers at each station (adjustable via traffic flow) set delays to ensure coverage

Specifications

•	Power typecompressed air and electricity
•	Chemical pickup typesupplied with pre-mixed solution
	from a central system solution
	Number of products unit can draw fromone product
•	Flow rate2 gal/min (7.6 l/min)
	Timer operation typerepeat cycle
•	Coverage areaONE NOZZLE: up to 9×5 ft. (2.7×1.5 m) TWO NOZZLES: up to 8×4 ft. (2.4×1.2 m) at each nozzle THREE NOZZLES: up to 6×3 ft. (1.8x0.9 m) at each nozzle
	Nozzle typetwin-line poly nozzle assembly (NZA-DS-TL-1)
	Number of nozzlesone control box can support
	up to 3 nozzle assemblies
	Distance from nozzles to control boxthe combined distance
	between control box and nozzle(s)
	must equal 100 ft. (30.5 m) or less
•	Tubing/fitting sizesdesigned for use with 1/2 in. (12.7 mm)
	outside diameter tubing between

Requirements

	5-10 CFM (141.6-283.2 l/min)
	Liquid temperature range40-100°F (4.4-37.8°C)
	Electrical requirements100-240 VAC, 50-60Hz, 1A
	Operating voltage24 VDC
•	Central system requirementspre-mixed solution must be
	supplied by a properly sized header system
	at 2 gpm and 40-80 psi (2.8-5.5 bar)
•	Chemical compatibilitychemical products
	used with this equipment must be formulated for this type of
	application and compatible with unit materials and pump seals. For
	morein formationonchemicalcompatibility, consult themanufacturer
	or SDS for your product or contact our customer service department.

· Compressed air requirements40-80 psi (2.8-5.5 bar) with