

Drum Lance

DL-33, DL-48, DL-54



The Good Stuff

- **Rigid delivery, to the last drop**
Rigid polypropylene that won't kink or curl, and a side-hole suction foot that draws chemistry to the very bottom
- **Universal drum compatibility**
Fits both fine and buttress drum openings with tool-free depth adjustment
- **Three lengths, one solution**
Available in 33 in., 48 in., and 54 in. to fit virtually any drum or tote depth

Features

- Made with chemical resistant polypropylene
- Fits both 2 in. NPS and 2 ½ in. buttress drum threads
- Vent hole prevents vacuum pressure buildup
- ¾ in. inside diameter pipe for high-volume pumping
- Rigid construction eliminates hose kinking
- Three hose barbs included: 3/8 in., 1/2 in., and 3/4 in.
- Check valve with Viton seals and Hastelloy spring
- Hastelloy mesh strainer
- Suction foot maintains draw at drum floor

Options

- Lance length
 - 33 in. (0.8 m)
 - 48 in. (1.2 m)
 - 54 in. (1.4 m)

Specifications

- Lance length/diameter.....33 in. (0.8 m), 48 in. (1.2 m), 54 in. (1.4 m)
with 3/4 in. (19.1 mm) diameter
- Drum Depth MountingDL-33 maximum drum depth of 35.9 in.
DL-48 maximum drum depth of 50.5 in.
DL-54 maximum drum depth of 56.5 in.
- Thread type2 in. NPS and 2 ½ in. buttress threads
- Fitting sizes3/8 in., 1/2 in., and 3/4 in. barbs included
- Seal TypeViton

Requirements

- Liquid temperature range.....40-100 °F (4.4-37.8 °C)
- Chemical compatibilitychemical products used with this equipment must be formulated for this type of application and compatible with unit materials and pump seals. For more information on chemical compatibility, consult the manufacturer or SDS for your product or contact our customer service department.

Industries

- Food and Beverage
- Agriculture
- Industrial



How to Buy



800 567 5420 | sales@foamit.com