

2.6 Gallon Foam Unit

F10.0L



Features

- Compact unit with manual pump
- Maximum portability for small jobs and spot cleaning
- Comfortable grip handle with trigger for quick on/off control
- Ability to switch between short and long wand assembly
- Pressure relief valve for safety
- Viton seals for chemical compatibility
- Natural color tank for easy visibility of product levels
- Product level fill markings in gallons and liters
- Extra wide stability base
- Vertical wand storage

Industries

- Institutional
- Food and Beverage
- Manufacturing



How to Buy

The Good Stuff

- **Small size, big foam**
Same high quality foam output FOAMit is known for, in a portable unit
- **Foam anywhere**
When you need to clean specific surfaces, our pump up foam unit is there. Apply foam with the adjustable wand assembly
- **Power in your hands**
Take the power of foam cleaning with you regardless of access to compressed air. A few pumps is all it takes to get the job done

Specs

- Power typemanual
- Chemical pickup typedraws from pre-mixed solution
- Number of products unit can draw from.....one product
- Capacity2.6 gallons (10 liters)
- Discharge line length/diameter: 6.5 ft. (2 m) hose, with 1/4 in. (6.4 mm) inside diameter
- Discharge wand/tip type polypropylene trigger handle with 17 in. (43.2 cm) wand extension and 110° fan tip
- Output distance.....1-3 ft. (0.3-0.9 m)
- Output volume1.00 gal/min (3.8 l/min)
- Flow rate.....0.2 gal/min (0.8 l/min)
- Pump sealsViton
- Run time from full tank approx. 10 minutes

Requirements

- Liquid temperature range 40-100° F (4.4-37.8° C)
- Chemical compatibilitychemical products used with this equipment must be formulated for this type of application and compatible with unit materials and pump seals. For more information on chemical compatibility, consult the manufacturer or SDS for your product or contact our customer service department.