

# 2.6 Gallon Dual-Power Foam Unit

F100



## The Good Stuff

- **Compressed air attachment**  
Connect to an air source to quickly pressurize the unit, then disconnect and move the unit to the area to be cleaned
- **Maximizing portability**  
Manual pump for when air isn't available. Dual operation with manual pump and connection for air supply allows for flexibility in applications
- **Natural tank**  
See chemical volume levels at a glance

## Specs

- Power type .....compressed air or manual
- Chemical pickup type .....draws from pre-mixed solution
- Number of products unit can draw from.....one product
- Capacity .....2.6 gallons (10 liters)
- Discharge line length/diameter ..... 6.5 ft. (2 m) hose, with 1/4 in. (6.4 mm) inside diameter
- Discharge wand/tip type ..... polypropylene trigger handle with 65 degree fan tip
- Output distance.....5-6 ft. (1.5-1.8 m)
- Output volume.....3 gal/min (11.4 l/min)
- Flow rate.....0.5 gal/min (1.9 l/min)
- Pump seals .....Viton

## Requirements

- Compressed air requirements..... 40 psi (2.8 bar) with 2-5 CFM (56.6-141.6 l/min)
- Liquid temperature range ..... 40-100 °F (4.4-37.8 °C)
- Chemical compatibility..... chemical products used with this equipment must be formulated for this type of application and compatible with unit materials and pump seals. For more information on chemical compatibility, consult the manufacturer or SDS for your product or contact our customer service department.

## Features

- Integrated attachment for compressed air
- Manual pump for when air isn't available
- 2.6 gallon (10 liter) capacity
- Viton seals for chemical compatibility
- Pressure regulator to not exceed set psi
- Built in pressure relief valve
- 6 foot discharge
- Natural color tank for easy visibility of products levels

## Industries

- Agriculture
- Institutional
- Industrial
- Food and Beverage



*How to Buy*



800 567 5420 | [sales@foamit.com](mailto:sales@foamit.com)