

20-gallon portable mist unit

FG-20N-3



the good stuff

- **efficient air consumption**
uses approx. 7.7 cfm, 80% more efficient than our competitors.
- **remote power off**
deactivate easily from a distance.
- **20-gallon tank**
our see through tank lets you know at a glance how much product has been dispensed.

features

- 3 nozzles mounted on fog mast
- see through tank – 20 gallon (75.7 liter) capacity
- quick-change pump
- hinged back plate provides tool-free access to components
- hinged lid, so you will never lose it
- front-facing drain for easy tank drainage
- in-line strainer to protect pump from debris

options

- color coding – Lid – 7 colors
(BK, BL, GN, YL, RD, PL, OR)
- pump seals: Santoprene, Viton, or Kalrez

industries

- institutional
- food and beverage
- manufacturing



how to buy

specs

- **power type**compressed air
- **chemical pickup type**.....draws from pre-mixed solution
- **number of products unit can draw from**one product
- **capacity**.....20 gallons (75.7 liters)
- **flow rate**.....3.7 gallons/hour per nozzle
(7.4 gallons/hour total with 2 nozzles)
- **pump seals** Santoprene, Viton, or Kalrez
- **droplet size**.....15 microns at 50 psi
- **coverage area**1 liter of solution will cover
approx. 1000 cubic feet
- **product height**.....47 inches (119.3 cm)
- **run time from full tank**.....approx. 2 hours
- **nozzle type**..... pneumatic fog nozzle
- **number of nozzles**3
- **fog mast height range**..... 3.5-8.5 ft. (1.1-2.6 m)
- **wheel type:**non-marking

requirements

- **compressed air requirements**.....50 psi with 7 cfm
- **liquid temperature range**..... 40-100 ° F (4.4-37 ° C)
- **chemical compatibility**.....chemical products
used with this equipment must be formulated for this type
of application and compatible with unit materials and pump
seals. For more information on chemical compatibility, con-
sult the manufacturer or SDS for your product or contact our
customer service department.

