

10 Gallon Battery Foam Unit With Polypropylene Trigger Handle

FI-10N-B



Features

- Draws from pre-mixed solution
- Battery operated
- Up to 45 minutes of continuous use from one charge
- Trigger gun handle with foam fan tip
- Hinged back plate provides tool-free access to components
- Natural color tank for easy visibility of product levels
- Hinged lid
- Integrated hose wraps
- Front-facing drain

Options

- Color coding
 - Lid – 9 colors (BK, BL, BN, GN, OR, PL, RD, WH, YL)
 - Discharge hose – 4 colors (BL, GN, YL, RD)

Industries

- Institutional
- Food and Beverage
- Manufacturing



How to Buy

The Good Stuff

- **Battery operated**
Battery operated that provides 45 minutes of continuous use from one charge
- **Trigger gun**
Includes a polypropylene trigger handle gun with a 50° fan tip
- **Configure with color**
Hoses and lids come in a variety of colors to match your chemical management systems and quickly tell units apart

Specs

- Power typeSLA battery
- Battery charge time 8 hours
- Battery run time 45 minutes of continuous use
- Chemical pickup typedraws from pre-mixed solution
- Number of products unit can draw fromone product
- Suction line diameter 3/8 in. (9.5 mm) inside diameter
- Capacity12.5 gallons (47.3 liters)
- Discharge line length/diameter12 ft. (3.7 m) hose, with 3/8 in. (9.5 mm) inside diameter
- Discharge wand/tip type polypropylene trigger handle with 50° fan tip
- Output distance5-6 ft. (1.5-1.8 m)
- Output volume3-3.5 gal/min (11.4-13.2 l/min) of foam
- Flow rateup to 1 gal/min (3.8 l/min)
- Pump seals Santoprene, Viton, or Kalrez
- Wheel type two 10 inch (25.4 cm) non-marking wheels

Requirements

- Liquid temperature range 40-100 ° F (4.4-37.8 ° C)
- Electrical requirements 120 VAC at 60 Hz, 1 amp (GFCI protected outlet) for battery charger only
- Operating voltage12 VDC
- Chemical compatibilitychemical products used with this equipment must be formulated for this type of application and compatible with unit materials and pump seals. For more information on chemical compatibility, consult the manufacturer or SDS for your product or contact our customer service department.



800 567 5420 | sales@foamit.com