

50 Gallon High Volume Foam Unit

FI-50NT-HV



Features

- 3/4 inch Teflon pump
- Natural color tank for easy visibility of product levels
- Hinged lid
- Integrated hose wrap
- Front-facing drain

Options

- Color coding
 - Lid – 9 colors (BK, BL, BN, GN, OR, PL, RD, WH, YL)

Industries

- Institutional
- Food and beverage
- Manufacturing

The Good Stuff

- **High output foam**
Provides high volume output for increased efficiency
- **Thick discharge hose**
Includes a 1 inch hose in diameter to fit its high output, allowing a greater foam expansion
- **Easy visibility of product levels**
This units has a natural color tank that allows you to identify product levels at a glance

Specs

- Power typecompressed air
- Chemical pickup typedraws from pre-mixed solution
- Number of products unit can draw from.....one product
- Suction line length/diameter 3/4 in. (19 mm) inside diameter
- Capacity50 gallons (189.3 liters)
- Discharge line length/diameter50 ft. (15.2 m) hose with 1 in. (25.4 mm) inside diameter
- Discharge wand/tip type 10 in. (25.4 cm) stainless steel wand with zero tip and ball valve
- Output distance.....40 ft. (12.2 m)
- Output volume92 gal/min (348.3 l/min) of foam
- Flow rate.....5 gal/min (18.9 l/min)
- Pump sealsTeflon
- Wheel type two 10 inch (25.4 cm) non-marking wheels, two 5 inch (12.7 cm) casters, one with lock

Requirements

- Compressed air requirements.....40-100 psi (2.8-6.9 bar) with 12-20 cfm (339.8-566.2 l/min)
- Liquid temperature range 40-100 ° F (4.4-37.8 ° C)
- Chemical compatibilitychemical products used with this equipment must be formulated for this type of application and compatible with unit materials and pump seals. For more information on chemical compatibility, consult the manufacturer or SDS for your product or contact our customer service department.



how to buy



800 567 5420 | sales@foamit.com