

15 Gallon Electric Foam Unit

FI-AC-15N



Features

- Draws from pre-mixed solution
- Powered by electricity (120 VAC)
- Handheld wand with 25 ft. (7.6 m) coiled discharge hose
- See through tank – 15 gallon (56.8 liter) capacity
- Built in air compressor
- Hinged back plate provides tool-free access to components
- Quick-change pump
- Hinged lid, so you will never lose it
- Front-facing drain for easy tank drainage
- In-line strainer to protect pump from debris

Options

- Lid – 9 colors (BK, BL, BN, GN, OR, PL, RD, WH, YL)
- Pump seals – 3 types (Santoprene, Viton, or Kalrez)

Industries

- Institutional
- Food and beverage
- Manufacturing



how to buy

The Good Stuff

- **On-board air compressor**
With an on-board compressor, this unit brings consistent foam volume to areas where compressed air isn't available
- **Portable power**
Equipped for 120 VAC, plug-in power: foam clean anywhere
- **15 gallon tank**
For larger cleaning operations, regardless of location. Get what you need, where you need it

Specs

- Power typeelectricity
- Chemical pickup typedraws from pre-mixed solution
- Number of products unit can draw fromone product
- Suction line length/diameter 3/8 in. (9.5 mm) inside diameter
- Capacity15 gallons (56.8 liters)
- Discharge line length/diameter
25 ft. (7.6 m) coiled twin-line tubing 1/4 in. (6.4 mm) od,
or 100 ft. (30.5) twin-line tubing 1/4 in. (6.4 mm) od
- Discharge wand/tip type polypropylene trigger handle
with 65° fan tip
- Output distance1-3 ft. (0.3-0.9 m)
- Output volume2.1 gal/min (7.9 l/min)
- Flow rate0.3 gal/min (1.1 l/min)
- Pump seals Santoprene, Viton, or Kalrez
- Run time from full tankapprox. 57 minutes
- Wheel typetwo 10 inch (25.4cm) non-marking wheels,
two 5 inch (12.7) casters, one with lock

Requirements

- Liquid temperature range 40-100 °F (4.4-37.8 °C)
- Electrical requirements120 VAC at 60 Hz, 8.5 amps
(GFCI protected outlet)
- Operating voltage120 VAC
- Chemical compatibilitychemical products
used with this equipment must be formulated for this type of
application and compatible with unit materials and pump seals. For
more information on chemical compatibility, consult the manufacturer
or SDS for your product or contact our customer service department.