

# portable 15-gallon foam unit

FI-AC-15N



## the good stuff

- **on-board air compressor**  
with an on-board compressor, the 15 Gallon Electric Foam Unit brings a consistent level of foam to areas where compressed air isn't available.
- **portable power**  
equipped for 120 VAC, plug in power: foam clean anywhere.
- **15 gallon tank**  
for larger cleaning operations, regardless of location. Get what you need, where you need it.

## features

- outputs a thin layer of thick, clinging foam
- draws from pre-mixed solution
- powered by electricity (120 VAC)
- see through tank – 15 gallon (56.8 liter) capacity
- handheld wand with 25 ft. (7.6 m) coiled discharge hose
- quick-change pump
- hinged back plate provides tool-free access to components
- hinged lid, so you will never lose it
- front-facing drain for easy tank drainage
- in-line strainer to protect pump from debris

## options

- color coding – Lid –  
7 colors (BK, BL, GN, YL, RD, PL, OR)
- pump seals: Santoprene, Viton, or Kalrez

## industries

- institutional
- food and beverage
- manufacturing



how to buy

 800 567 5420 | sales@foamit.com

## specifications

- **power type** ..... electricity
- **chemical pickup type** ..... draws from pre-mixed solution
- **number of products unit can draw from** ..... one product
- **suction line length/diameter** ..... 3/8 in. (9.5 mm) inside diameter
- **capacity** ..... 15 gallons (56.8 liters)
- **discharge line length/diameter:** .....  
25 ft. (7.6 m) coiled twin-line tubing 1/4 in. (6.4 mm) outside diameter, or 100 ft. (30.5) twin-line tubing 1/4 in. (6.4 mm) outside diameter
- **discharge wand/tip type** ..... polypropylene trigger handle with 65° fan tip
- **output distance** ..... 1-3 ft. (0.3-0.9 m)
- **output volume** ..... 2.1 gal/min (7.9 l/min)
- **flow rate** ..... 0.3 gal/min (1.1 l/min)
- **pump seals** ..... Santoprene, Viton, or Kalrez
- **run time from full tank** ..... Approx. 57 minutes
- **wheel type:** ..... Two 10 inch (25.4cm) non-marking wheels, two 5 inch (12.7) casters with lock

## requirements

- **liquid temperature range** ..... 40-100° F (4.4-37° C)
- **Electrical requirements** ..... 120 VAC at 60 Hz, 8.5 amps (GFCI protected outlet)
- **Operating voltage** ..... 120 VAC
- **chemical compatibility** ..... chemical products used with this equipment must be formulated for this type of application and compatible with unit materials and pump seals. For more information on chemical compatibility, consult the manufacturer or SDS for your product or contact our customer service department.