

# Battery Powered Rover Foam Unit

FI-BP-RVR



## Features

- Draws from pre-mixed solution
- Battery powered – no air lines or power cords to hold you back
- Up to 50 minutes of continuous run time from one charge
- To extend usage time, additional batteries can be used
- Easy-to-read battery level indicator on the battery
- Removable cover allows easy serviceability
- Ideal for drain foaming, spot cleaning, and more
- 10 ft. (3 m) of coiled tubing extends coverage without tangling or dragging
- Natural color tank for easy visibility of product levels
- In-line strainer to protect pump from debris
- Splash proof battery box for battery protection
- Integrated wand holster for clean, convenient storage

## Options

- Color coding
  - Cap – 9 colors (BK, BL, BN, GN, OR, PL, RD, WH, YL)

## Industries

- Institutional
- Healthcare
- Life Science
- Food and Beverage



*How to Buy*

## The Good Stuff

- **Battery protection**  
Specially designed splash box keeps the lithium-ion battery secure and dry
- **Easy portability**  
Four swivel casters and ergonomic handle make this 5-gallon unit effortless to move between locations
- **Integrated wand holster**  
Removable and washable holster keeps the wand secure, accessible and drip-free

## Specs

- Power type.....lithium-ion battery
- Battery charge time .....2 hours
- Battery run time.....up to 50 minutes of continuous use
- Chemical pickup type .....draws from pre-mixed solution
- Number of products unit can draw from.....one product
- Suction line diameter ..... 3/8 in. (9.5 mm) inside diameter
- Capacity .....5 gallons (18.9 liters)
- Discharge line length/diameter .....10 ft. (3 m) coiled hose,  
with 3/8 in. (9.5 mm) inside diameter
- Discharge wand/tip type ..... polypropylene spray gun  
with 80° fan tip
- Output distance.....up to 5 ft. (1.5 m)
- Output volume .....4.2 gal/min (15.9 L/min)
- Flow rate.....0.8 gal/min (3 L/min)
- Pump seals ..... Santoprene diaphragm, Viton check seals
- Wheel type .....four 3 inch (7.6 cm) casters

## Requirements

- Liquid temperature range.....40-100 °F (4.4-37.8 °C)
- Electrical requirements ..... 120-240 VAC at 50-60 Hz, 3 amps  
(GFCI protected outlet) for battery charger only
- Operating voltage.....24 VDC
- Chemical compatibility.....chemical products  
used with this equipment must be formulated for this type of application and compatible with unit materials and pump seals. For more information on chemical compatibility, consult the manufacturer or SDS for your product or contact our customer service department.



800 567 5420 | [sales@foamit.com](mailto:sales@foamit.com)