

Battery Powered Ultra-Low Volume Foam Unit

FI-BPULV



The Good Stuff

- **Lithium-ion battery**
Fast-charging battery extends run time while minimizing downtime
- **Small size, big performance**
High quality spray output in a portable unit
- **Mighty in durability**
Crafted with robust, corrosion-resistant materials, these units are built to last

Features

- Draws from pre-mixed solution
- Battery powered – no air lines or power cords to hold you back
- Up to 60 minutes of use from one charge
- Integrated hose wraps

Requirements

- **Liquid temperature range**.....40-100 °F (4.4-37.8 °C)
- **Electrical requirements** Input: 12.6VDC 2A 25.2W
Charger Input: 100-240VAC at 50-60Hz 1.5A
(GFCI protected outlet) for battery charger only
- **Operating voltage** 12 VDC
- **Chemical compatibility** chemical products used with this equipment must be formulated for this type of application and compatible with unit materials and pump seals. For more information on chemical compatibility, consult the manufacturer or SDS for your product or contact our customer service department.

Specs

- **Power type**.....battery
- **Battery charge time**1 hour 40 minutes
- **Battery run time** up to 60 minutes of continuous use
- **Chemical pickup type**.....draws from pre-mixed solution
- **Number of products unit can draw from**one product
- **Capacity**0.3 gallons (1 liter)
- **Discharge line length/diameter**4.5 ft. (1.4 m) tube with 1/4 in. (6.4 mm) outside diameter
- **Discharge wand/tip type**polypropylene trigger valve with 80 degree fan tip
- **Output volume**0.41 gal/min (1.6 l/min)
- **Flow rate/usage**.....0.07 gal/min (0.3 l/min)
- **Pump seals**EPDM diaphragm / EPDM check seals
- **Product height** 15.3 in. (388.6 mm)
- **Run time from full tank** Approx. 4 min.
- **Number of nozzles**.....one
- **Tubing/fitting sizes**.....1/4 in. (6.4 mm) tube



How to Buy



800 567 5420 | sales@foamit.com