

# 15 gallon concentrate foam unit for 2-part products

FI-CN-15N-2P



## the good stuff

- **easy to use, easy to maintain**  
designed for portability, efficiency, and hassle-free maintenance. Our quick-change pump and tool-free, hinged access plate reduce downtime when a repair is needed.
- **two solutions, one unit**  
pulls 2-part chemistry from two chemical jugs simultaneously.
- **configure with color**  
lids and hoses come in a variety of colors to match your chemical management systems and quickly tell units apart in your chemical cage.

## features

- draws from two concentrated products simultaneously
- ideal for 2-part products that need to be mixed on the fly
- dilutes at ratios of 8:1 to 150:1 (water:chemical) for each product
- powered by compressed air
- holds two of our chemical jugs or other chemical containers
- onboard water tank – 15 gallon (56.8 liter) capacity
- hinged back plate provides tool-free access to components
- quick-change pump
- hinged lid
- anti-kink hose protection
- natural color tank for easy visibility of water levels
- integrated hose wraps
- front-facing drain
- in-line strainer to protect pump from debris

## options

- color coding
  - lid – 7 colors (BK, BL, GN, YL, RD, PL, OR)
  - discharge hose – 4 colors (BL, GN, YL, RD)

## industries

- food and beverage
- manufacturing



how to buy

## specs

- power type .....compressed air
- chemical pickup type..... draws from concentrated product
- dilution ratio range .....8:1 to 150:1 for each product  
Note: Dilution rate can be set independently for each product
- number of products unit can draw from ..... two products,  
simultaneously
- suction line length/diameter..... two 8 ft. (2.4 m) clear hose  
with 1/4 in. (6.4 mm) inside diameter
- capacity ..... 15 gallons (56.8 liters) of water;  
up to 10 gallons (37.9 liters) of concentrate
- discharge line length/diameter.....30 ft. (9 m) hose,  
with 3/4 in. (19 mm) inside diameter
- discharge wand/tip type .....7 in. (17.8 cm) stainless steel wand  
with zero tip and ball valve
- output distance.....25-30 ft. (7.6-9.1 m)
- output volume..... 20-45 gal/min (75.7-170.3 l/min)
- flow rate .....2-2.25 gal/min (7.6-8.5 l/min)
- pump seals ..... Santoprene, Viton, or Kalrez
- wheel type: ..... two 10 inch (25.4 cm) non-marking wheels  
and two 5 inch (12.7 cm) casters, one with lock

## requirements

- Compressed air requirements.....40-80 psi (2.8-5.5 bar)  
with 5-10 cfm (141.6-283.2 l/min)
- liquid temperature range..... 40-100 °F (4.4-37.8 °C)
- chemical compatibility.....chemical products  
used with this equipment must be formulated for this type of application and compatible with unit materials and pump seals.  
For more information on chemical compatibility, consult the manufacturer or SDS for your product or contact our customer service department.



800 567 5420 | sales@foamit.com