

EZBlend Foam Unit

FI-EZB-15NV



Features

- Pre-set to dilute Sterilex products at labeled rate of 1:1:10 to 1:1:8 – no setup required
- Includes two 5 gallon chemical jugs with quick-connect suction fittings
- User-friendly color coding on jugs and unit corresponds to Sterilex solution 1 and 2
- Foam wand with fan tip for efficient surface coverage - ideal for environmental cleaning and disinfecting food contact surfaces
- Quick connect wand can be easily interchanged with optional FOAMit attachments for drain foaming
- On-board water tank – 15 gallon (56.8 liter) capacity
- Powered by compressed air
- Hinged back plate provides tool-free access to components
- Quick-change pump
- Hinged lid, available in 9 colors
- Anti-kink hose protection
- Translucent tank and jugs allow visibility of fill levels
- Integrated hose wraps
- Front-facing drain
- In-line strainer to protect pump from debris
- Designed for use with EZBlend Chemical Transfer Unit

Industries

- Food and beverage
- Manufacturing



how to buy

The Good Stuff

- **Part of Sterilex EZBlend System**
Draws from concentrated Sterilex products and dilutes on the fly to prevent waste
- **No need to premix**
Only activate what you use, as you use it
- **Save time with fewer refills**
Two 5 gallon jugs of concentrate will make 45-50 gallons (170-189 liters) of solution.
Just refill the water tank and keep foaming

Specs

- **Power type**compressed air
- **Chemical pickup type**draws from concentrated product
- **Dilution ratio range**.....12.8-16 fl. oz. : 12.8-16 fl. oz. : 1 gallon
(378.5-473.2 ml : 378.5-473.2 ml : 3.8 liters)
- **Number of products unit can draw from**.....two products, simultaneously
- **Suction line length/diameter**two transparent suction lines, one blue one green, each 4 ft. (1.2 m) long with 1/4 in. (6.4 mm) id; with quick disconnect fittings for chemical jugs
- **Capacity**15 gallons (56.8 liters) of water; up to 10 gallons (37.9 liters) of concentrate
- **Discharge line length/diameter**30 ft. (9 m) hose, with 3/4 in. (19 mm) inside diameter
- **Discharge wand/tip type**12 in. (30.5 cm) stainless steel wand and ball valve with 65° fan tip; includes stainless quick connects
- **Output distance**.....10-12 ft. (3-4.6 m)
- **Output volume**15-20 gal/min (56.8-75.7 l/min)
- **Flow rate**.....2 gal/min (7.6 l/min)
- **Pump seals**Viton
- **Wheel type**two 10 inch non-marking wheels, two 5 inch casters, one with lock

Requirements

- **Compressed air requirements**.....40-80 psi ((2.8-5.5 bar) with 5-10 cfm (141.6-283.2 l/min)
- **Liquid temperature range**40-100 ° F (4.4-37.8 ° C)
- **Chemical compatibility**this unit is specifically configured for use with Sterilex liquid products.



800 567 5420 | sales@foamit.com