

ezblend foam unit

FI-EZB-15NV



the good stuff

- **part of Sterilex EZBlend System**
draws from concentrated Sterilex products and dilutes on the fly to prevent waste.
- **no need to premix**
only activate what you use, as you use it.
- **save time with fewer refills**
two 5 gallon jugs of concentrate will make 45-50 gallons (170-189 liters) of solution. Just refill the water tank and keep foaming.

features

- pre-set to dilute Sterilex products at labeled rate of 1:1:10 to 1:1:8 – no setup required
- includes two 5 gallon chemical jugs with quick-connect suction fittings
- user-friendly color coding on jugs and unit corresponds to Sterilex solution 1 and 2
- foam wand with fan tip for efficient surface coverage – ideal for environmental cleaning and disinfecting food contact surfaces
- quick connect wand can be easily interchanged with optional FOAM-iT attachments for drain foaming
- onboard water tank – 15 gallon (56.8 liter) capacity
- powered by compressed air
- hinged back plate provides tool-free access to components
- quick-change pump
- hinged lid, available in 5 colors
- anti-kink hose protection
- translucent tank and jugs allow visibility of fill levels
- integrated hose wraps
- front-facing drain
- in-line strainer to protect pump from debris
- designed for use with EZBlend Chemical Transfer Unit

specs

- **power type** compresses air
- **chemical pickup type**..... draws from concentrated product
- **dilution ratio range** 12.8-16 fl. oz. : 12.8-16 fl. oz. : 1 gallon
(378.5-473.2 ml : 378.5-473.2 ml : 3.78 liters)
- **number of products unit can draw from** Two products, simultaneously
- **suction line length/diameter** two transparent suction lines, one blue and one green, each 4 ft. (1.2 m) long with 1/4 in. (6.4 mm) inside diameter; with quick disconnect fittings for chemical jugs
- **capacity** 15 gallons (56.78 liters) of water; up to 10 gallons (37.85 liters) of concentrate
- **discharge line length/diameter:** 30 ft. (9 m) hose, with 3/4 in. (19 mm) inside diameter
- **discharge wand/tip type:** 12 in. (30.48 cm) stainless steel wand and ball valve with 65° fan tip; includes stainless quick connects
- **output distance** 10-12 ft. (3-4.6 m)
- **output volume** 15-20 gal/min (56.8-75.7 l/min)
- **flow rate** 2 gal/min (7.6 l/min)
- **pump seals** Viton
- **wheel type:** two 10 inch non-marking wheels, two 5 inch casters with lock

requirements

- **Compressed air requirements** 40-80 psi (3-5 bar) with 5-10 cfm (141-283 l/min)
- **liquid temperature range** 40-100° F (4.4-37° C)
- **chemical compatibility** this unit is specifically configured for use with Sterilex liquid products.

industries

- food and beverage
- manufacturing



how to buy



800 567 5420 | sales@foamit.com