

Pre-Mix Foam Unit

FI-WALL



Features

- Draws from pre-mixed solution
- Powered by compressed air
- Stainless steel ball valve and wand
- Stainless steel fluid fittings
- Quick-change pump

Options

- Color coding
 - Discharge hose – 4 colors (BL, GN, YL, RD)

Industries

- Institutional
- Food and beverage
- Manufacturing

The Good Stuff

- **50 ft. discharge hose**
Unit comes with 50ft. of discharge hose to maximize your reach
- **Draws from pre-mixed solution**
Draws product from pre-mixed solution, just drop your suction line and go
- **Configure with color**
Hoses come in a variety of colors to match your chemical management systems and quickly tell units apart

Specs

- Power type.....compressed air
- Chemical pickup type.....draws from pre-mixed solution
- Number of products unit can draw from.....one product
- Suction line length/diameter 8 ft. (2.4 m) hose with
3/8 in. (9.5 mm) inside diameter
- Discharge line length/diameter50 ft. (15.2 m) hose with
3/4 in. (19 mm) inside diameter
- Discharge wand/tip type7 in. (17.8 cm) stainless steel wand
with zero tip and ball valve
- Output distance.....25-30 ft. (7.6-9.1 m)
- Output volume20-45 gal/min (75.7-170.3 l/min) of foam
- Flow rate.....2 gal/min (7.6 l/min)
- Pump seals Santoprene, Viton, or Kalrez

Requirements

- Compressed air requirements..... 40-80 psi (2.8-5.5 bar) with
5-10 cfm (141.6-283.2 l/min)
- Liquid temperature range 40-100 ° F (4.4-37.8 ° C)
- Chemical compatibilitychemical products
used with this equipment must be formulated for this type of
application and compatible with unit materials and pump seals. For
more information on chemical compatibility, consult the manufacturer
or SDS for your product or contact our customer service department.



how to buy



800 567 5420 | sales@foamit.com