

pre-mix foam unit

FI-WALL



Features

- draws from pre-mixed solution
- powered by compressed air
- stainless steel ball valve and wand
- stainless steel fluid fittings
- quick-change pump

options

- color coding
 - discharge hose – 4 colors (BL, GN, YL, RD)

industries

- institutional
- food and beverage
- manufacturing

the good stuff

- **50 ft. discharge hose**
unit comes with 50ft. of discharge hose to maximize your reach.
- **draws from pre-mixed solution**
draws product from pre-mixed solution, just drop your suction line and go
- **configure with color**
hoses come in a variety of colors to match your chemical management systems and quickly tell units apart

specs

- power typecompressed air
- chemical pickup type.....draws from pre-mixed solution
- number of products unit can draw fromone product
- suction line length/diameter..... 8 ft. (2.4 m) hose with 3/8 in. (9.5 mm) inside diameter
- discharge line length/diameter:.....50 ft. (15 m) hose, with 3/4 in. (19 mm) inside diameter
- discharge wand/tip type7 in. (17.8 cm) stainless steel wand with zero tip and ball valve
- output distance..... 25-30 ft. (7-9 m)
- output volume.....20-45 gal/min (75-170 l/min) of foam
- flow rate*2 gal/min (7.6 l/min)
- pump seals Santoprene, Viton, or Kalrez

requirements

- Compressed air requirements..... 40-80 psi (3-5 bar) with 5-10 cfm (141-283 l/min)
- Liquid temperature range 40-100 ° F (4.4-37 ° C)
- Chemical compatibilityChemical products used with this equipment must be formulated for this type of application and compatible with unit materials and pump seals. For more information on chemical compatibility, con-sult the manufacturer or SDS for your product or contact our cus-tomer service department.



how to buy



800 567 5420 | sales@foamit.com