


# Central Dual Foam System

FIFI-STN



## Features

- Drop station for central foam system
- Pump and nozzles sold separately
- Two foam systems built inside a shared enclosure
  - Systems must run independently
- Powered by compressed air
- Stainless steel ball valve and wand
- Stainless steel fluid fittings
- Ability to add padlock to box
- Includes stainless steel hose hanger

## Options

- Pump sold separately
- Color coding
  - Discharge hose – 4 colors (BL, GN, YL, RD)

## Industries

- Food and Beverage
- Manufacturing



How to Buy

## The Good Stuff

- **Secure Central Chemical Location**  
Keep chemistry secure, away from the production floor; no need to refill containers, chemistry given on demand
- **No Refills**  
One location to titrate consistent chemical
- **On Demand Chemical**  
Save time and labor, just grab the hose and foam, it's that simple

## Specifications

- Power type .....central system
- Chemical pickup type.....supplied with pre-mixed solution  
from a central station
- Number of products unit can draw from.....two products
- Discharge line length/diameter .....50 ft. (15 m) hose with  
3/4 in. (19 mm) inside diameter
- Discharge wand/tip type .....7 in. (17.8 cm) stainless steel wand  
with zero tip and ball valve
- Output distance.....25-30 ft. (7.6-9.1 m)
- Output volume ..... 20-45 gal/min (75.7-170.3 l/min)
- Flow rate..... 2 gal/min (7.6 l/min)
- Product height .....18 in. (45.7 cm)
- Tubing/fitting sizes ..... 4 ft. (1.2 m) chemical inlet hose with 1/2 in.  
(12.7 mm) inside diameter and 1 lb check valve

## Requirements

- Compressed air requirements ..... 40-80 psi (2.8-5.5 bar) with  
5-10 cfm (141.6-283.2 l/min)
- Liquid temperature range .....40-100 ° F (4.4-37.8 ° C)
- Central system requirements.....pre-mixed solution must be  
supplied by a properly sized header system  
at 2 GPM and 40 to 80 psi (2.8 to 5.5 bar)
- Chemical compatibility .....chemical products  
used with this equipment must be formulated for this type of  
application and compatible with unit materials and pump seals. For  
more information on chemical compatibility, consult the manufacturer  
or SDS for your product or contact our customer service department.