

# 30 Gallon Gel Unit With Agitator

GI-30N-AM



## Features

- Draws from pre-mixed solution
- Powered by compressed air
- Air operated agitator to continually mix product in tank
- Hinged back plate provides tool-free access to components
- Quick-change pump
- Natural color tank for easy visibility of product levels
- Integrated hose wraps
- Front-facing drain
- Fan tip wand assembly for increased coverage
- Anti-kink hose protection

## Options

- Color coding
  - Discharge hose – 4 colors (BL, GN, YL, RD)

## Industries

- Food and beverage
- Manufacturing



*how to buy*

## The Good Stuff

- **Easy to use, easy to maintain**  
Designed for portability, efficiency, and hassle-free maintenance. Our quick-change pump and tool-free, hinged access plate reduce downtime when a repair is needed
- **Natural tank**  
See chemical volume levels at a glance
- **Configure with color**  
Hoses come in a variety of colors to match your chemical management systems and quickly tell units apart in your chemical cage

## Specs

- **Power type**.....compressed air
- **Chemical pickup type**.....draws from pre-mixed solution
- **Number of products unit can draw from** .....one product
- **Suction line diameter** ..... 3/8 in. (9.5 mm) inside diameter
- **Capacity** ..... 30 gallons (113.6 liters)
- **Discharge line length/diameter** .....30 ft. (9 m) hose, with 1/2 in. (12.7 mm) inside diameter
- **Discharge wand/tip type** .....24 in. (60.9 cm) stainless steel wand with fan tip and ball valve (spray tips included: ST1510SS, ST2520SS, and ST4008SS)
- **Output distance**.....6-10 ft. (1.8-3 m)
- **Output volume** ..... 0.8-2 gal/min (3-7.6 l/min)
- **Flow rate**.....2 gal/min (7.6 l/min)
- **Pump seals** ..... Santoprene, Viton, or Kalrez
- **Wheel type** ..... two 10 inch (25.4 cm) non-marking wheels, two 5 inch (12.7 cm) casters, one with lock

## Requirements

- **Compressed air requirements**.....40-80 psi (2.8-5.5 bar) with 15-18 cfm (424.8-509.7 l/min)
- **Liquid temperature range** ..... 40-100 °F (4.4-37.8 °C)
- **Chemical compatibility**.....chemical products used with this equipment must be formulated for this type of application and compatible with unit materials and pump seals. For more information on chemical compatibility, consult the manufacturer or SDS for your product or contact our customer service department.



800 567 5420 | [sales@foamit.com](mailto:sales@foamit.com)