

# 30 gallon gel unit with agitator

GI-30N-AM



## the good stuff

- **easy to use, easy to maintain**  
designed for portability, efficiency, and hassle-free maintenance. Our quick-change pump and tool-free, hinged access plate reduce downtime when a repair is needed
- **natural tank**  
see chemical volume levels at a glance
- **configure with color**  
hoses come in a variety of colors to match your chemical management systems and quickly tell units apart in your chemical cage

## features

- draws from pre-mixed solution
- powered by compressed air
- air operated agitator to continually mix product in tank
- hinged back plate provides tool-free access to components
- quick-change pump
- natural color tank for easy visibility of product levels
- integrated hose wraps
- front-facing drain
- fan tip wand assembly for increased coverage
- anti-kink hose protection

## options

- color coding  
– discharge hose – 4 colors (BL, GN, YL, RD)

## industries

- food and beverage
- manufacturing

## specs

- **power type** .....compressed air
- **chemical pickup type**.....draws from pre-mixed solution
- **number of products unit can draw from** .....one product
- **suction line length/diameter**..... 3/8 in. (9.5 mm) inside diameter
- **capacity** ..... 30 gallons (113.6 liters)
- **discharge line length/diameter:**.....30 ft. (9 m) hose,  
with 1/2 in. (12.7 mm) inside diameter
- **discharge wand/tip type** ..... 24 in. (60.9 cm) stainless steel wand  
with fan tip and ball valve  
(spray tips included: ST1510, ST2508, and ST4008)
- **output distance**.....6-10 ft. (1.8-3 m)  
(varies due to viscosity of product)
- **output volume** ..... 0.8-2 gal/min (3-7.6 l/min)  
(varies due to viscosity of product and fan tip size)
- **flow rate** .....2 gal/min (7.6 l/min)  
(varies based on spray tip used)
- **pump seals** ..... Santoprene, Viton, or Kalrez
- **wheel type:** ..... two 10 inch non-marking wheels,  
two 5 inch casters, one with lock

## requirements

- **compressed air requirements**.....40-80 psi (2.8-5.5 bar)  
with 15-18 cfm (424.8-509.7 l/min)
- **liquid temperature range**..... 40-100 ° F (4.4-37.8 ° C)
- **chemical compatibility**.....chemical products  
used with this equipment must be formulated for this type of application and compatible with unit materials and pump seals. For more information on chemical compatibility, consult the manufacturer or SDS for your product or contact our customer service department.



how to buy



800 567 5420 | sales@foamit.com