

10-gallon portable mist unit

MU-10N-2



Features

- 2 nozzles mounted on unit handle
- see through tank – 10 gallon (37.8 liter) capacity
- quick-change pump
- hinged back plate provides tool-free access to components
- hinged lid, so you will never lose it
- front-facing drain for easy tank drainage
- in-line strainer to protect pump from debris

options

- color coding – Lid – 7 colors
(BK, BL, GN, YL, RD, PL, OR)
- pump seals: Santoprene, Viton, or Kalrez

industries

- institutional
- food and beverage
- manufacturing



how to buy

the good stuff

- **efficient air consumption**
uses 7 cfm, 80% more efficient than our competitors.
- **dual mist nozzles**
mounted on the unit handle with a droplet size of 15 microns at 50 psi.
- **10-gallon tank**
our see through tank lets you know at a glance how much product has been dispensed.

specs

- **power type**compressed air
- **chemical pickup type**.....draws from pre-mixed solution
- **number of products unit can draw from**one product
- **capacity**.....12.5 gallons (37.8 liters)
- **flow rate**.....3.7 gallons/hour per nozzle
(7.4 gallons/hour total with 2 nozzles)
- **pump seals** Santoprene, Viton, or Kalrez
- **droplet size**.....15 microns at 50 psi
- **coverage area**1 liter of solution will cover
approx. 1000 cubic feet
- **product height**.....41 inches (104 cm)
- **run time from full tank**.....approx. 1.5 hours
- **nozzle type**.....pneumatic mist nozzle
- **number of nozzles**2
- **wheel type:**non-marking

requirements

- **compressed air requirements**.....50 psi with 7 cfm
- **liquid temperature range**.....40-100 ° F (4.4-37 ° C)
- **chemical compatibility**.....chemical products used with this equipment must be formulated for this type of application and compatible with unit materials and pump seals. For more information on chemical compatibility, consult the manufacturer or SDS for your product or contact our customer service department.

