

20-gallon portable mist unit

MU-20N-3



the good stuff

- **efficient air consumption**
uses approx. 9 cfm, 80% more efficient than our competitors.
- **telescoping misting mast**
insures fog chemistry fills a space, large or small
- **20-gallon tank**
our see through tank lets you know at a glance how much product has been dispensed.

features

- 3 misting nozzles mounted on a mast
- see through tank – 20 gallon (47.32 liter) capacity
- quick-change pump
- hinged back plate provides tool-free access to components
- hinged lid, so you will never lose it
- front-facing drain for easy tank drainage
- in-line strainer to protect pump from debris

options

- color coding – Lid – 7 colors
(BK, BL, GN, YL, RD, PL, OR)
- pump seals: Santoprene, Viton, or Kalrez

industries

- institutional
- food and beverage
- manufacturing



how to buy

specs

- power typecompressed air
- chemical pickup type.....draws from pre-mixed solution
- number of products unit can draw fromone product
- capacity.....20 gallons (47.32 liters)
- flow rate3.7 gallons/hour per nozzle
(11.1 gallons/hour total with 3 nozzles)
- pump seals Santoprene, Viton, or Kalrez
- droplet size15 microns at 50 psi
- coverage area1 liter of solution will cover
approx. 1000 cubic feet
- product height.....47 inches (119.3 cm)
- run time from full tank.....approx. 2 hours
- nozzle type.....pneumatic mist nozzle
- number of nozzles3
- fog mast height range.....3.5-8.5 ft. (1.1-2.6 m)
- wheel type:non-marking

requirements

- compressed air requirements.....50 psi with 9 cfm
- liquid temperature range.....40-100 ° F (4.4-37 ° C)
- chemical compatibility.....chemical products used with this equipment must be formulated for this type of application and compatible with unit materials and pump seals. For more information on chemical compatibility, consult the manufacturer or SDS for your product or contact our customer service department.

