

2.6 gallon air-powered mist unit

MU100-PSGN130



the good stuff

- **hard surface cleaning in a blast**
disinfect high traffic surfaces faster and more ergonomically than pull-trigger sprayers.
- **wide application of chemical**
nozzle guarantees a wide and even distribution of cleaning chemical where it's needed.
- **clean more, more efficiently**
from bar rooms to locker rooms, quickly apply chemical to everything, even funky surfaces like chairs and door knobs.

Features

- handheld misting wand allows for controlled, manual application to critical surfaces
- fine spray application allows for product movement into areas not commonly treated by traditional application methods
- draws from pre-mixed solution
- powered by compressed air – requires air connection to operate (cannot be powered by manual pump or tank pressure)
- handheld wand with 12 ft. (3.7 m) coiled discharge hose
- see through tank – 2.6 gallon (10 liter) capacity
- pressure regulator and pressure relief valve for safety
- viton seals for chemical compatibility
- product level fill markings in gallons and liters
- extra wide stability base

industries

- institutional
- kitchens
- food retail



how to buy

specifications

- **power type**compressed air
- **chemical pickup type**.....draws from pre-mixed solution
- **number of products unit can draw from**one product
- **capacity**.....2.6 gallons (10 liters)
- **discharge line length/diameter:**.....
12 ft. (3.6 m) coiled twin-line tubing 1/4 in. (6.4 mm) outside diameter, red and blue, with 0.16 in. (4.06 mm) inside diameter
- **discharge wand/tip type** polypropylene trigger handle for liquid output, polypropylene fog/mist nozzle with Kynar tip
- **output distance**.....3 ft. to 4 ft. 6 in.
- **output volume**.....8.79 oz/min at 40 psi
- **flow rate**.....8.79 oz/min at 40 psi
- **pump seals**Viton
- **run time from full tank**.....Approx. 38 minutes
- **nozzle type**.....pneumatic mist nozzle
- **number of nozzles**one

requirements

- **compressed air requirements**.....40-80 psi (3-5 bar) with 2-5 cfm (57-142 l/min)
- **liquid temperature range**..... 40-100 ° F (4.4-37 ° C)
- **chemical compatibility**.....chemical products used with this equipment must be formulated for this type of application and compatible with unit materials and pump seals. For more information on chemical compatibility, consult the manufacturer or SDS for your product or contact our customer service department.



800 567 5420 | sales@foamit.com