

Battery Powered Rover Spray Unit

SP-BP-RVR



Features

- Draws from pre-mixed solution
- Battery powered – no air lines or power cords to hold you back
- Up to 3 hours and 15 minutes of continuous use from one charge
- To extend usage time, additional batteries can be used
- Easy-to-read battery level indicator on the battery
- Removable cover allows easy serviceability
- 10 ft. (3 m) of coiled tubing extends coverage without tangling or dragging
- Natural color tank for easy visibility of product levels
- In-line strainer to protect pump from debris
- Splash proof battery box for battery protection
- Integrated wand holster for clean, convenient storage

Options

- Color coding
– Cap – 9 colors (BK, BL, BN, GN, OR, PL, RD, WH, YL)

Industries

- Institutional
- Healthcare
- Life Science
- Food and Beverage



How to Buy

The Good Stuff

- **Battery protection**
Specially designed splash box keeps the lithium-ion battery secure and dry
- **Easy portability**
Four swivel casters and ergonomic handle make this 5-gallon unit effortless to move between locations
- **Integrated wand holster**
Removable and washable holster keeps the wand secure, accessible and drip-free

Specs

- Power type.....lithium-ion battery
- Battery charge time2 hours
- Battery run time.....up to 3 hours and 15 minutes of continuous use
- Chemical pickup typedraws from pre-mixed solution
- Number of products unit can draw from.....one product
- Suction line diameter..... 3/8 in. (9.5 mm) inside diameter
- Capacity5 gallons (18.9 liters)
- Discharge line length/diameter10 ft. (3 m) coiled hose, with 3/8 in. (9.5 mm) inside diameter
- Discharge wand/tip typepolypropylene spray gun with 25° fan tip
- Output distance.....up to 8 ft. (2.4 m)
- Output volume0.8 gal/min (3 L/min)
- Flow rate.....0.8 gal/min (3 L/min)
- Pump sealsSantoprene diaphragm, Viton check seals
- Wheel typefour 3 inch (7.6 cm) casters

Requirements

- Liquid temperature range 40-100 °F (4.4-37.8 °C)
- Electrical requirements 120-240 VAC at 50-60 Hz, 3 amps (GFCI protected outlet) for battery charger only
- Operating voltage.....24 VDC
- Chemical compatibility.....chemical products used with this equipment must be formulated for this type of application and compatible with unit materials and pump seals. For more information on chemical compatibility, consult the manufacturer or SDS for your product or contact our customer service department.