

Battery Powered Ultra-Low Volume Spray Unit

SP-BPULV



The Good Stuff

- **Lithium-ion battery**
Fast-charging battery extends run time while minimizing downtime
- **Small size, big performance**
High quality spray output in a portable unit
- **Mighty in durability**
Crafted with robust, corrosion-resistant materials, these units are built to last

Features

- Draws from pre-mixed solution
- Battery powered – no air lines or power cords to hold you back
- Up to 5 hours of use from one charge
- Designed for application of Forever Wet chemical
- Integrated hose wraps

Requirements

- **Liquid temperature range**.....40-100 °F (4.4-37.8 °C)
- **Electrical requirements** Input: 12.6VDC 2A 25.2W
Charger Input: 100-240VAC at 50-60Hz 1.5A
(GFCI protected outlet) for battery charger only
- **Operating voltage**12 VDC
- **Chemical compatibility**..... chemical products used with this equipment must be formulated for this type of application and compatible with unit materials and pump seals. For more information on chemical compatibility, consult the manufacturer or SDS for your product or contact our customer service department.

Specs

- **Power type**.....battery
- **Battery charge time**.....1 hour 40 minutes
- **Battery run time**.....up to 5 hours of continuous use
- **Chemical pickup type**.....draws from pre-mixed solution
- **Unit weight empty**.....approx. 5.1 lbs (2.3 kg)
- **Unit weight full**.....approx. 7.5 lbs (3.4 kg)
- **Fluid capacity**.....0.3 gallons (1 liter)
- **Discharge wand/tip type**..... Polypropylene trigger valve with 80 degree fan tip
- **Discharge function**..... spray discharge
- **Discharge length/diameter**.....4.5 ft. (1.4 m) tube with 1/4 in. (6.4 mm) outside diameter
- **Output volume**.....0.1 gal/min (0.4 l/min)
- **Flow rate/usage**.....0.1 gal/min (0.4 l/min)
- **Pump seals**.....EPDM diaphragm / EPDM check seals
- **Run time from full tank**.....approx. 3 min.
- **Tubing/fitting sizes**.....1/4 in. (6.4 mm) tube



How to Buy



800 567 5420 | sales@foamit.com