

# pre-mix spray unit with all-poly fittings

SP-WALL-AP



## Features

- all-poly fluid fittings to increase chemical compatibility
- draws from pre-mixed solution
- powered by compressed air
- quick-change pump
- poly spray gun wand with fan tip

## options

- color coding
  - discharge hose – 4 colors (BL, GN, YL, RD)

## industries

- institutional
- food and beverage
- manufacturing

## the good stuff

- **polypropylene trigger gun**  
the polypropylene trigger gun is easy-to-use and highly durable
- **draws from pre-mixed solution**  
draws product from pre-mixed solution, just drop your suction line and go
- **configure with color**  
hoses come in a variety of colors to match your chemical management systems and quickly tell units apart

## specs

- power type .....compressed air
- chemical pickup type.....draws from pre-mixed solution
- number of products unit can draw from .....one product
- suction line length/diameter..... 8 ft. (2.4 m) hose with  
3/8 in. (9.5 mm) inside diameter
- discharge line length/diameter:.....50 ft. (9 m) hose,  
with 3/8 in. (9.5 mm) inside diameter
- discharge wand/tip type ..... polypropylene trigger handle  
with 25° fan tip
- output distance.....10-12 ft. (3.0-3.7 m)
- output volume.....2 gal/min (7.6 l/min)
- flow rate\* .....2 gal/min (7.6 l/min)
- pump seals ..... Santoprene, Viton, or Kalrez
- fluid fittings type .....all-poly

## requirements

- Compressed air requirements..... 40-80 psi (3-5 bar) with 2 cfm  
(56.6 l/min) (141-283 l/min)
- Liquid temperature range ..... 40-100° F (4.4-37° C)
- Chemical compatibility.....chemical products  
used with this equipment must be formulated for this type  
of application and compatible with unit materials and pump  
seals. For more information on chemical compatibility,  
con-sult the manufacturer or SDS for your product or contact  
our cus-tomer service department.



*how to buy*



800 567 5420 | [sales@foamit.com](mailto:sales@foamit.com)