

Pre-Mix Spray Unit

SP-WALL



Features

- Draws from pre-mixed solution
- Powered by compressed air
- Quick-change pump
- Poly spray gun wand with fan tip

Options

- Color coding
 - Discharge hose – 4 colors (BL, GN, YL, RD)

Industries

- Institutional
- Food and beverage
- Manufacturing

The Good Stuff

- **Polypropylene spray gun**
The polypropylene spray gun is easy-to-use and highly durable
- **Draws from pre-mixed solution**
Draws product from pre-mixed solution, just drop your suction line and go
- **Configure with color**
Hoses come in a variety of colors to match your chemical management systems and quickly tell units apart

Specs

- Power typecompressed air
- Chemical pickup typedraws from pre-mixed solution
- Number of products unit can draw fromone product
- Suction line length/diameter 8 ft. (2.4 m) hose with 3/8 in. (9.5 mm) inside diameter
- Discharge line length/diameter50 ft. (15.2 m) hose with 3/8 in. (9.5 mm) inside diameter
- Discharge wand/tip typepolypropylene spray gun with 25° fan tip
- Output distance.....10-12 ft. (3.0-3.7 m)
- Output volume2 gal/min (7.6 l/min)
- Flow rate.....2 gal/min (7.6 l/min)
- Pump seals Santoprene, Viton, or Kalrez

Requirements

- Compressed air requirements.....40-80 psi (2.8-5.5 bar) with 2 cfm (56.6 l/min)
- Liquid temperature range 40-100 ° F (4.4-37.8 ° C)
- Chemical compatibilitychemical products used with this equipment must be formulated for this type of application and compatible with unit materials and pump seals. For more information on chemical compatibility, consult the manufacturer or SDS for your product or contact our customer service department.



how to buy



800 567 5420 | sales@foamit.com