

pre-mix spray unit

SP-WALL



Features

- draws from pre-mixed solution
- powered by compressed air
- quick-change pump
- poly spray gun wand with fan tip

options

- color coding
 - discharge hose – 4 colors (BL, GN, YL, RD)

industries

- institutional
- food and beverage
- manufacturing

the good stuff

- **polypropylene trigger gun**
the polypropylene trigger gun is easy-to-use and highly durable
- **draws from pre-mixed solution**
draws product from pre-mixed solution, just drop your suction line and go
- **configure with color**
hoses come in a variety of colors to match your chemical management systems and quickly tell units apart

specs

- power typecompressed air
- chemical pickup typedraws from pre-mixed solution
- number of products unit can draw fromone product
- suction line length/diameter 8 ft. (2.4 m) hose with 3/8 in. (9.5 mm) inside diameter
- discharge line length/diameter:50 ft. (9 m) hose, with 3/8 in. (9.5 mm) inside diameter
- discharge wand/tip type polypropylene trigger handle with 25° fan tip
- output distance10-12 ft. (3.0-3.7 m)
- output volume2 gal/min (7.6 l/min)
- flow rate*2 gal/min (7.6 l/min)
- pump seals Santoprene, Viton, or Kalrez

requirements

- Compressed air requirements 40-80 psi (3-5 bar) with 2 cfm (56.6 l/min) (141-283 l/min)
- Liquid temperature range 40-100 °F (4.4-37 °C)
- Chemical compatibilitychemical products used with this equipment must be formulated for this type of application and compatible with unit materials and pump seals. For more information on chemical compatibility, con-sult the manufacturer or SDS for your product or contact our cus-tomer service department.



how to buy



800 567 5420 | sales@foamit.com