

Pre-Mix Spray Unit With All-Poly Fittings

SP-WL-AP



Features

- All-poly fluid fittings to increase chemical compatibility
- Draws from pre-mixed solution
- Powered by compressed air
- Quick-change pump
- Poly spray gun wand with fan tip

Options

- Color coding
 - Discharge hose – 4 colors (BL, GN, YL, RD)

Industries

- Institutional
- Food and beverage
- Manufacturing



how to buy

The Good Stuff

- **Polypropylene spray gun**
The polypropylene spray gun is easy-to-use and highly durable
- **Draws from pre-mixed solution**
Draws product from pre-mixed solution, just drop your suction line and go
- **Configure with color**
Hoses come in a variety of colors to match your chemical management systems and quickly tell units apart

Specs

- Power type.....compressed air
- Chemical pickup typedraws from pre-mixed solution
- Number of products unit can draw from.....one product
- Suction line length/diameter 8 ft. (2.4 m) hose with
3/8 in. (9.5 mm) inside diameter
- Discharge line length/diameter50 ft. (15.2 m) hose with
3/8 in. (9.5 mm) inside diameter
- Discharge wand/tip type polypropylene spray gun
with 25° fan tip
- Output distance.....10-12 ft. (3.0-3.7 m)
- Output volume2 gal/min (7.6 l/min)
- Flow rate.....2 gal/min (7.6 l/min)
- Pump seals Santoprene, Viton, or Kalrez
- Fluid fittings type.....all-poly

Requirements

- Compressed air requirements.....40-80 psi (2.8-5.5 bar)
with 2 cfm (56.6 l/min)
- Liquid temperature range 40-100 ° F (4.4-37.8 ° C)
- Chemical compatibility.....chemical products
used with this equipment must be formulated for this type of
application and compatible with unit materials and pump seals. For
more information on chemical compatibility, consult the manufacturer
or SDS for your product or contact our customer service department.



800 567 5420 | sales@foamit.com