

# Pre-Mix Spray Unit

SP-WL



## Features

- Draws from pre-mixed solution
- Powered by compressed air
- Quick-change pump
- Poly spray gun wand with fan tip

## Options

- Color coding
  - Discharge hose – 4 colors (BL, GN, YL, RD)

## Industries

- Institutional
- Food and Beverage
- Manufacturing



*How to Buy*

## The Good Stuff

- **Polypropylene spray gun**  
The polypropylene spray gun is easy-to-use and highly durable
- **Draws from pre-mixed solution**  
Draws product from pre-mixed solution, just drop your suction line and go
- **Configure with color**  
Hoses come in a variety of colors to match your chemical management systems and quickly tell units apart

## Specs

- Power type.....compressed air
- Chemical pickup type.....draws from pre-mixed solution
- Number of products unit can draw from .....one product
- Suction line length/diameter ..... 8 ft. (2.4 m) hose with  
3/8 in. (9.5 mm) inside diameter
- Discharge line length/diameter .....50 ft. (15.2 m) hose with  
3/8 in. (9.5 mm) inside diameter
- Discharge wand/tip type .....polypropylene trigger handle  
with 25° fan tip
- Output distance.....10-12 ft. (3.0-3.7 m)
- Output volume .....2 gal/min (7.6 l/min)
- Flow rate.....2 gal/min (7.6 l/min)
- Pump seals ..... Santoprene, Viton, or Kalrez

## Requirements

- Compressed air requirements.....40-80 psi (2.8-5.5 bar)  
with 2 CFM (56.6 l/min)
- Liquid temperature range ..... 40-100 °F (4.4-37.8 °C)
- Chemical compatibility.....chemical products  
used with this equipment must be formulated for this type of  
application and compatible with unit materials and pump seals. For  
more information on chemical compatibility, consult the manufacturer  
or SDS for your product or contact our customer service department.



800 567 5420 | sales@foamit.com