# 2.6 Gallon Dual-Power **Spray Unit**

SP100





## **Features**

- Dual operation with manual pump and connection for air supply for flexibility in applications
- Connect to an air source to pressurize the unit, then disconnect and move the unit to the area to be cleaned
- · Lightweight, durable, and chemical-resistant discharge hose
- Pressure regulator and pressure relief valve for safety
- Viton seals for chemical compatibility
- Natural color tank for easy visibility of product levels
- Heavy duty trigger gun with 40° fan tip

# **Industries**

- Institutional
- · Aviation
- · Food and Beverage · Agriculture
- Manufacturing
- Remediation



How to buy

## The Good Stuff

#### **Maximizing portability**

The convenience of air power, with the small footprint of a manual pump up unit. Dual operation with manual pump and connection for air supply allows for flexibility in applications

#### **Natural tank**

See chemical volume levels at a glance

## Heavy duty wand

Tough and lightweight. A highly durable trigger wand, made with ultra-high molecular weight polyethylene

# **Specs**

•	Power typecompressed air or manual
•	Chemical pickup typedraws from pre-mixed solution
•	Number of products unit can draw fromone product
•	Capacity2.6 Gallons (10 liters)
•	Discharge line length/diameter:6 ft. (1.8 M) hose,
	with 1/4 in. (6.4 Mm) inside diameter
•	Discharge wand/tip typepolypropylene trigger handle
	with 40° fan tip
•	Output distance1-4 ft. (0.3-1.2 m)
•	Output volume
•	Flow rate
•	Pump sealsviton
•	Product height23.5 Inches (61 cm)

## Requirements

•	Compressed air requirements40 psi (2.8 bar)
	with 2-5 cfm (56.6-141.6 l/min)
•	Liquid temperature range40-100°f (4.4-37.8°C)
•	Chemical compatibilitychemical products
	used with this equipment must be formulated for this type of
	application and compatible with unit materials and pump seals. For
	moreinformationonchemicalcompatibility, consultthemanufacturer
	or SDS for your product or contact our customer service department.