

Footwear sanitizing unit with boot scrubber



SS2-MBS



the good stuff

- **boot scrubber**
boot scrubber allows you knock off any unwanted sludge before sanitizing.
- **low moisture**
helps keep moisture out of unwanted areas while still providing sanitation to the soles of shoes and boots.
- **transition zones**
effective sanitation in high traffic entryways or transition zones.

features

- easy-to-use sanitation for entryways and transition zones
- low-moisture system
- air-operated pump delivers a consistent amount of sanitizer (0.2 oz/5.91 mL) per spray
- spray pattern ensures even coverage across shoe sole
- collection basin is easy to access or swap out for cleaning
- spray guard prevents overspray
- draws from pre-mixed solution
- includes 2.5 gallon jug with suction hose
- stainless steel handle and base provide stability for user
- boot scrubber helps remove excess debris

specs

- power typecompressed air
- chemical pickup type.....draws from pre-mixed solution
- number of products unit can draw fromone product
- suction line length/diameter..... 3 ft. (0.9 m) clear hose with 1/4 in. (6.4 mm) inside diameter
- output volume.....0.2 oz. (5.91 mL)
- flow rate*.....0.2 oz. (5.91 mL)
- pump seals.....Viton
- number of nozzles..... 4 nozzles

requirements

- Compressed air requirements..... 40-80 psi (3-5 bar) with 5-10 cfm (141-283 l/min)
- Liquid temperature range 40-100 ° F (4.4-37 ° C)
- Chemical compatibility.....chemical products used with this equipment must be formulated for this type of application and compatible with unit materials and pump seals. For more information on chemical compatibility, con-sult the manufacturer or SDS for your product or contact our cus-tomer service department.

industries

- institutional
- food and beverage
- manufacturing
- aviation
- agriculture
- remediation



how to buy



800 567 5420 | sales@foamit.com