

# 20 Gallon Transfer Unit with Heavy Duty Ball Valve



TU-20N-SSW



## Features

- Heavy duty ball valve (SSW)
- Transfer each product up to 3.5 gal/min (13.2 l/min)
- Chemically-resistant PVC hose
- Air regulator with filter
- Air operated diaphragm pump with quick release hose barbs
- In-line strainer to protect pump from debris
- Choose Santoprene, Viton, or Kalrez pump seals

## Options

- Color coding
  - Lid – 9 colors (BK, BL, BN, GN, OR, PL, RD, WH, YL)

## Industries

- Food and Beverage
- Industrial

## The Good Stuff

- **Highly portable**  
Reliable chemistry transfer no matter the location
- **Heavy duty ball valve**  
Maximum durability for any volume transfer
- **Labor saving**  
Eliminates hand carrying jugs, reducing the risk of chemical exposure, and saving labor time

## Specs

- Power type .....compressed air
- Chemical pickup type .....Draws from pre-mixed or concentrated solution
- Number of products unit can draw from .....one product
- Suction line diameter .....1/2 in. (12.7 mm) inside diameter
- Capacity .....20 gallons (75.7 liters)
- Discharge line length/diameter .....15 ft. (4.6 m) hose with 1/2 in. (12.7 mm) inside diameter
- Discharge wand/tip type .....10 in. (25.4 cm) stainless steel wand with zero tip and ball valve
- Flow rate .....3.5 gal/min (13.2 l/min)
- Pump seals .....Santoprene, Viton, Kalrez
- Wheel type .....two 10 inch (25.4 cm) non-marking wheels

## Requirements

- Compressed air requirements.....20-80 psi (1.4-5.5 bar) with 2 CFM (56.6 l/min)
- Liquid temperature range.....40-100 ° F (4.4-37.8 ° C)
- Chemical compatibility.....chemical products used with this equipment must be formulated for this type of application and compatible with unit materials and pump seals. For more information on chemical compatibility, consult the manufacturer or SDS for your product or contact our customer service department.



How to Buy



800 567 5420 | sales@foamit.com