

25 Gallon Transfer Unit with Heavy Duty Ball Valve

TU-25N-SSW



Features

- Heavy duty ball valve (SSW)
- Transfer each product up to 3.5 gal/min (13.2 l/min)
- Chemically-resistant PVC hose
- Air regulator with filter
- Air operated diaphragm pump with quick release hose barbs
- In-line strainer to protect pump from debris
- Choose Santoprene, Viton, or Kalrez pump seals

Options

- Color coding
 - Lid – 9 colors (BK, BL, BN, GN, OR, PL, RD, WH, YL)

Industries

- Food and beverage
- Industrial

The Good Stuff

- **Highly portable**
Reliable chemistry transfer no matter the location
- **Heavy Duty Ball Valve**
Maximum durability for any volume transfer
- **Labor saving**
Eliminates hand carrying jugs, reducing the risk of chemical exposure, and saving labor time

Specs

- Power typecompressed air
- Chemical pickup typedraws from pre-mixed or concentrated solution
- Number of products unit can draw fromone product
- Suction line diameter 1/2 in. (12.7 mm) inside diameter
- Capacity25 gallons (94.6 liters)
- Discharge line length/diameter: 15 ft. (4.6 m) hose with 1/2 in. (12.7 mm) inside diameter
- Discharge wand/tip type 10 in. (25.4 cm) stainless steel wand with zero tip and ball valve
- Flow rate3.5 gal/min (13.2 l/min)
- Pump seals Santoprene, Viton, Kalrez
- Wheel type two 10 inch (25.4 cm) non-marking wheels, two 3 inch (7.6 cm) casters, one with lock

Requirements

- Compressed air requirements..... 20-80 psi (1.4-5.5 bar) with 2 CFM (56.6 l/min)
- Liquid temperature range..... 40-100° f (4.4-37.8° c)
- Chemical compatibility.....chemical products used with this equipment must be formulated for this type of application and compatible with unit materials and pump seals. For more information on chemical compatibility, consult the manufacturer or SDS for your product or contact our customer service department.



how to buy



800 567 5420 | sales@foamit.com